

# DRYDOCK® Rain Sealing System

## Product Specifications



### DESIGN HIGHLIGHTS

- Protects dock from moisture infiltration, keeping products safe from costly water damage
- Automatic position, no manual activation necessary
- Heavy-duty galvanized steel channel head frame
- Translucent fiberglass raked head frame for fast water drainage
- High-resilient foam core protected by three layers of durable coated fabric
- Seal is easily replaceable, reducing down time and maintenance costs
- Rugged support brackets for mounting over existing equipment
- Weighted side covers provide extra protection for the dock area (not shown)
- Covers trucks 12'-9" to 13'-6" high

### APPLICATION DATA

Door width: \_\_\_\_\_ ft. \_\_\_\_\_ in.

Door height: \_\_\_\_\_ ft. \_\_\_\_\_ in.

Dock height: \_\_\_\_\_ ft. \_\_\_\_\_ in.

Bumper protection\*: \_\_\_\_\_ in.

(\*Includes bumper projection and any building wall/foundation offset or cantilever)

### TRUCKS AND TRAILERS SERVICED

Width: \_\_\_\_\_ Max. \_\_\_\_\_ Min.

Height: \_\_\_\_\_ Max. \_\_\_\_\_ Min.

Length: \_\_\_\_\_ Max. \_\_\_\_\_ Min.

Hydraulic tailgate: ☐ Yes ☐ No

Rear step section: ☐ Yes ☐ No

Tailgate/step section size: \_\_\_\_\_ in

Yard jockeys: ☐ Yes ☐ No

### PROJECT INFORMATION

JOB NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

GENERAL CONTRACTOR \_\_\_\_\_

DISTRIBUTOR \_\_\_\_\_

QUANTITY \_\_\_\_\_

### CERTIFIED FOR CONSTRUCTION

BY \_\_\_\_\_

COMPANY \_\_\_\_\_

ADDRESS \_\_\_\_\_

DATE \_\_\_\_\_

