



ENTRE/MATIC

Serco Heavy-duty 2" Insulated Sectional Door SE2432



www.sercoentrematic.com



Built from heavy-duty solid steel to survive in tough commercial environments.

Two tough steel skins with CFC-free polystyrene insulation sandwiched between make the Serco SE2432 a strong, efficient and durable door. Add tongue and groove construction, weather-stripping, and a thermal break that provides a strong barrier from extreme heat and cold for an efficient 4-step insulation system.


The 24-gauge steel outer skin features shallow ribs and a stucco embossment. On the interior, 27-gauge steel is also embossed with a stucco pattern to help hide daily wear.



CONSTRUCTION

R-Value 9.05 Serco SE2432
Heavy-duty, 2" insulated steel door

**TRIPLE-LAYER
Steel + Insulation + Steel**



Track: All doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit www.sercoentrematic.com.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

Hardware: Hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

SPECIFICATIONS

	Heavy-duty
	Serco SE2432
STEEL THICKNESS (Front/Back)	24-ga / 27-ga
PANEL DESIGN	Ribbed
STEEL EMBOSSMENT	Stucco
DOOR THICKNESS	2" (5.1 cm)
CONSTRUCTION LAYERS	Triple
INSULATION ¹	Polystyrene
R-VALUE ²	9.05
MINIMUM WIDTH	6'
MAXIMUM WIDTH	24' 2"
MINIMUM HEIGHT	7'
MAXIMUM HEIGHT	24' 1"
WIND LOAD ³ AVAILABLE	•
PAINT FINISH WARRANTY ⁴	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing. ² Calculated door section R-value is in accordance with DASMA TDS-163. ³ It is your responsibility to make sure your garage door meets local building codes. ⁴ For complete warranty details, visit sercoentrematic.com or contact your local Serco dealer.


PANEL



RIBBED PANEL WITH STUCCO EMBOSSMENT

COLORS

Serco steel doors are pre-painted; for custom colors, exterior latex paint must be used. Visit sercoentrematic.com for instructions on painting. Actual paint colors may vary from samples shown.



WINDOW OPTIONS



24" X 12" INSULATED GLASS
Available with either a black or white frame.



24" X 6" DOUBLE INSULATED
ACRYLIC WINDOWS WITH BLACK FRAME



Entrematic
165 Carriage Court
Winston-Salem, NC 27105
800.933.4834
www.sercoentrematic.com



Entrematic reserves the right to change specifications and designs without notice and without incurring obligations. Entrematic products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Serco as word and logo are registered trademarks belonging to Entrematic Group AB or other companies controlled by the same organization. All rights reserved.

©Entrematic Group AB 2015. All rights reserved. Printed in USA Form # SSS-HD2ISD-1015