

SLT Series Lift Table

Product Specifications



DESIGN HIGHLIGHTS

- Hand-held NEMA 4X push button with 10' straight cord
- Maintenance strut
- Self lubricating bushings
- Wire braided hydraulic hoses
- Solid steel legs with hard chromed pins
- Pre-wired power unit with UL approved control panel
- Velocity fuses on all cylinders to prevent uncontrolled descent
- Polyethylene reservoir allows easy visual check of oil level or steel reservoir with dip stick
- 1 HP single phase with 115 VAC control valve
- Meets or exceeds the ANSI MH29.1 standard for industrial scissors lifts

PROJECT INFORMATION

JOB NAME _____

ADDRESS _____

GENERAL CONTRACTOR _____

DISTRIBUTOR _____

MODEL _____ QUANTITY _____

VOLTAGE/PHASE _____

AVAILABLE OPTIONS

- Oversized platforms with straight sides
- Oversized platform with beveled toe guards (add 8" to length and width. lowered height increases to 8 1/2")
- Accordion skirting (platform must be 6" longer and wider than standard)
- Remote air operated power unit. requires 70psi and 95cfm clean plant air; includes hand valve NEMA 4 washdown power unit and controls
- Increased horsepower available
- 1 HP 3 phase
- NEMA 12, wall mount up/down push button station
- Upper travel limit switch
- High cycle package
- Wall mount push button station
- Foot switch with cover - NEMA 1
- Portability
- Other _____

DIMENSIONS								
MODEL No.	TRAVEL [inches]	CAPACITY [lb]	PLATFORM & BASE FRAME [inches]	MAXIMUM PLATFORM SIZE [inches]	LOWERED HEIGHT [inches]	RAISED HEIGHT [inches]	RAISE LOWER TIME [sec]	SHIP WEIGHT [lb]
SLT24-2	24	2,000	24 x 36	48 x 58	7	31	18	455
SLT24-4	24	4,000	24 x 36	48 x 58	8	32	25	640
SLT24-6	24	6,000	30 x 36	48 x 58	8	32	54	780
SLT24-8	24	8,000	36 x 36	48 x 58	10	34	62	890
SLT36-2	36	2,000	24 x 48	48 x 60	7	43	24	619
SLT36-4	36	4,000	24 x 48	48 x 60	9	45	48	710
SLT36-6	36	6,000	30 x 48	48 x 60	9	45	72	970
SLT36-8	36	8,000	36 x 48	48 x 60	12	48	81	1,340
SLT48-2	48	2,000	24 x 72	48 x 96	8	56	35	960
SLT48-4	48	4,000	24 x 72	48 x 96	9	57	70	1,000
SLT48-6	48	6,000	30 x 72	48 x 96	9	57	105	1,430
SLT48-8	48	8,000	36 x 72	48 x 96	12	60	138	1,984
SLT48-10	48	10,000	36 x 72	48 x 96	12	60	154	2,144
SLT59-2	59	2,000	24 x 88	48 x 102	8	67	40	1,207
SLT59-4	59	4,000	24 x 88	48 x 102	9	68	80	1,470
SLT59-6	59	6,000	30 x 88	48 x 102	9	68	120	1,850
SLT59-8	59	8,000	36 x 88	48 x 102	12	71	159	2,540
SLT59-10	59	10,000	36 x 88	48 x 102	12	71	201	2,740

Non-standard platform sizes, consult factory



Sercodock
 1612 Hutton Drive, Suite 140
 Carrollton, TX 75006
 800.933.4834
www.sercodockproducts.com

4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Sercodock as word and logo are registered trademarks belonging to ASSA ABLOY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.

©ASSA ABLOY. All rights reserved. Part of ASSA ABLOY. Printed in USA. Form # SPS-LILT-0121