

# SRL Series Rail Lift

## Product Specifications



### DESIGN HIGHLIGHTS

- Low profile for surface-mounted applications
- No pit construction required
- Three-sided platform
- Heavy-duty I-beam deck understructure
- Excellent end-load stability in fully raised position
- Displacement style cylinder with internal stops
- Self-contained power unit/control panel
- Standard pre-wired control panel
- NEMA 4X push-button controller with 15' cord
- Superior speed-to-horsepower ratio compared to scissor-style dock lifts
- Direct thrust cylinder provide constant speed through full range of travel
- Checker plate or smooth deck surface
- Sealed guide bearing rollers
- Fused 24-volt control circuit
- 18" bridge
- 30" stationary ramp with lagging angles
- Bolt on handrail
- Hydraulic system pressure gauge

### AVAILABLE OPTIONS

- |   |   |
|---|---|
| <input type="checkbox"/> Upper travel limit switch  | <input type="checkbox"/> Aluminum bridges     |
| <input type="checkbox"/> In motor warning beeper and flashing light on a post X 60" high or wall mounted on bracket | <input type="checkbox"/> Larger steel bridges |
| <input type="checkbox"/> Interlocking gate  | <input type="checkbox"/> Power pack cover     |
|   | <input type="checkbox"/> Other _____          |

### PROJECT INFORMATION

JOB NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

GENERAL CONTRACTOR \_\_\_\_\_

DISTRIBUTOR \_\_\_\_\_

MODEL \_\_\_\_\_ QUANTITY \_\_\_\_\_

VOLTAGE/PHASE \_\_\_\_\_

### CERTIFIED FOR CONSTRUCTION

BY \_\_\_\_\_

COMPANY \_\_\_\_\_

ADDRESS \_\_\_\_\_

DATE \_\_\_\_\_

DIMENSIONS					
MODEL No.	LIFT CAPACITY [lbs]	DECK SIZE [in]	FEET PER MINUTE [fpm]	HP	SHIP. WEIGHT [lb]
SRL45-4	4,000	48 x 60	13	5	2,050
SRL46-4	4,000	48 x 72	13	5	2,200
SRL55-4	4,000	60 x 60	13	5	2,150
SRL56-4	4,000	60 x 72	13	5	2,500
SRL57-4	4,000	60 x 84	13	5	2,650
SRL58-4	4,000	60 x 96	13	5	2,800
SRL66-4	4,000	72 x 72	13	5	2,800
SRL67-4	4,000	72 x 84	13	5	2,950
SRL68-4	4,000	72 x 96	13	5	3,100
SRL610-4	4,000	72 x 120	13	5	3,300
SRL612-4	4,000	72 x 144	13	5	3,600
SRL45-6	6,000	48 x 60	12	5	2,200
SRL46-6	6,000	48 x 72	12	5	2,400
SRL55-6	6,000	60 x 60	12	5	2,400
SRL56-6	6,000	60 x 72	12	5	2,750
SRL57-6	6,000	60 x 84	12	5	2,875
SRL58-6	6,000	60 x 96	12	5	3,000
SRL66-6	6,000	72 x 72	12	5	3,100
SRL67-6	6,000	72 x 84	12	5	3,250
SRL68-6	6,000	72 x 96	12	5	3,400
SRL610-6	6,000	72 x 120	12	5	3,700
SRL612-6	6,000	72 x 144	12	5	3,900



**SercO**  
 1612 Hutton Drive, Suite 140  
 Carrollton, TX 75006  
 800.933.4834  
[www.sercodockproducts.com](http://www.sercodockproducts.com)

4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. SercO as word and logo are registered trademarks belonging to ASSA ABLOY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.