

SZL Series Zero Lift Table

Product Specifications



DESIGN HIGHLIGHTS

- 1 HP power unit - 115v/1ph/60hz with UL/CSA approved electrical panel
- NEMA 4X hand control with 10 ft of cable
- Self lubricating bushings with hardened chrome pins for pivot points
- Velocity fuses on cylinders to prevent uncontrolled descent
- Up travel limit switch
- Maintenance blocks

AVAILABLE OPTIONS

- Foot switch with cover - NEMA 1
- In motor warning beeper and flashing light on a post X 36" high or wall mounted bracket
- Increased horsepower available
- Stainless steel
- Hand rails
- Transition bridge
- Three phase power
- Accordion skirting
- Other _____

Model Number	Travel (inches)	Capacity (lbs.)	Standard Platform (inches)	Overall Dimension (inches)	Deck Lowered Height (inches)	Deck Raised Height (inches)	Raise Lower Time (seconds)	Ship Weight (lbs.)
SZL30-2	30	2,000	50W x 48L	72W x 54L	0.50	30.50	30	1,380
SZL30-4		4,000	50W x 48L	72W x 54L	0.50	30.50	52	1,650
SZL40-2	40	2,000	50W x 60L	72W x 66L	0.50	40.50	37	1,620
SZL40-4		4,000	50W x 60L	72W x 66L	0.50	40.50	60	1,800

PROJECT INFORMATION

JOB NAME _____

ADDRESS _____

GENERAL CONTRACTOR _____

QUANTITY _____

DISTRIBUTOR _____

MODEL _____

VOLTAGE/PHASE _____



Serco
 1612 Hutton Drive, Suite 140
 Carrollton, TX 75006
 800.933.4834
 www.sercodockproducts.com

4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Serco as word and logo are registered trademarks belonging to ASSA ABLOY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.