


SDL Series Surface Mounted Dock Lift

Product Specifications



DESIGN HIGHLIGHTS

- High tensile strength, structural tubing construction for maximum stability
- Velocity fuses on lift cylinders prevent lift from free falling in the event of hydraulic failure
- Pre-wired NEMA-4X push button control panel
- Versatile, split entry plates with lifting chains and entry ramp
- Removable, mandrel formed tubing handrails
- Maintenance strut
- Removable lifting lugs
- Meets ANSI MH29.1 safety requirements for industrial scissor lifts
- Upper travel limit switch
- Oil sight gauge in hydraulic reservoir
- Self-lubricating bushings
- Standard 25' hydraulic hose
- Low temperature oil
- Two-year parts, one-year labor limited warranty
- UL approved panel

PROJECT INFORMATION

JOB NAME _____

ADDRESS _____

GENERAL CONTRACTOR _____

DISTRIBUTOR _____

MODEL _____ QUANTITY _____

VOLTAGE/PHASE _____

CERTIFIED FOR CONSTRUCTION

BY _____

COMPANY _____

ADDRESS _____

DATE _____

AVAILABLE OPTIONS

- | | |
|--|--|
| <input type="checkbox"/> Portability | <input type="checkbox"/> Roller curtain |
| <input type="checkbox"/> Electric toe guard | <input type="checkbox"/> Accordion bellow skirting |
| <input type="checkbox"/> Aluminum bridge plates | <input type="checkbox"/> Mechanical pop-up stop |
| <input type="checkbox"/> Post office option package | <input type="checkbox"/> Biodegradable oil |
| <input type="checkbox"/> Hot dipped galvanized | <input type="checkbox"/> Special sizes |
| <input type="checkbox"/> Spring-assisted bridge | <input type="checkbox"/> Other _____ |
| <input type="checkbox"/> In-motion warning beeper and flashing light | |

DIMENSIONS									
MODEL No.	TRAVEL [inches]	CAPACITY [lb]	STANDARD PLATFORM [in]	MAX. END LOAD [lb]	MAX. SIDE LOAD [lb]	LOWERED HEIGHT [inches]	HP	RAISE LOWER SPEED [rpm]	SHIP WEIGHT [lb]
SDL47-4SM	52	4,000	48x84	2,400	2,000	7	3	12	2,400
SDL47-5SM	52	5,000	48x84	3,000	2,500	7	3	10	2,550
SDL47-6SM	52	6,000	48x84	3,600	3,000	7	3	10	2,650
SDL57-4SM	52	4,000	60x84	2,400	2,000	7	3	15	2,500
SDL57-5SM	52	5,000	60x84	3,000	2,500	7	3	10	2,650
SDL57-6SM	52	6,000	60x84	3,600	3,000	7	3	10	2,750
SLD67-4SM	52	4,000	72x84	2,400	2,000	7	3	9	2,850
SDL68-5SM	52	5,000	72x96	2,500	2,500	7	3	9.5	2,850
SDL68-8SM	52	8,000	72x96	4,000	4,000	8	3	8	4,500
SDL610-5SM	52	5,000	72x120	2,500	2,500	7	3	8	3,500
SDL612-12SM	*52	6,000	72x144	6,000	6,000	8	10	9	6,500



Sercodock
1612 Hutton Drive, Suite 140
Carrollton, TX 75006
800.933.4834
www.sercodockproducts.com

4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Sercodock as word and logo are registered trademarks belonging to ASSA ABLOY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.

©ASSA ABLOY. All rights reserved. Part of ASSA ABLOY. Printed in USA. Form # SPS-LDLM-0725